

Report Information
from Dialog DataStar



Table of Contents

DataStar Documents.....	1
Chemical routes to improved mechanical properties of PECVD low k thin films.....	1
Search Strategy.....	3

Chemical routes to improved mechanical properties of PECVD low k thin films.

Accession number & update

0008331397 20051201.

Conference information

Materials, Technology and Reliability for Advanced Interconnects and Low-k Dielectrics-2004, San Francisco, CA, USA, 13-15 April 2004.

Source

Materials, Technology and Reliability for Advanced Interconnects and Low-k Dielectrics-2004 (Materials Research Society Symposium Vol.812), 2004, p. 109-14, 4 refs, pp. xiii+402. Publisher: Materials Research Soc, Warrendale, PA, USA.

Author(s)

Bilodeau-S-M, Borovik-A-S, Ebbing-A-A, Vestyck-D-J, Xu-C, Roeder-J-F, Baum-T-H. Editor(s): Carter-R-J, Hau-Riege-C-S, Kloster-G-M, Lu-T-M, Schulz-S-E.

Author affiliation

Bilodeau, S.M., Borovik, A.S., Ebbing, A.A., Vestyck, D.J., Xu, C., Roeder, J.F., Baum, T.H., ATMI Inc., Danbury, CT, USA.

Abstract

Increasing the elastic modulus and **hardness** of low k films is one of the key challenges towards integration of these materials into future integrated circuits. Several approaches are explored for increasing the **hardness** of carbon doped oxide (**CDO**) dielectrics. Several low k precursors and their mixtures specifically chosen to enhance the **hardness** (H) and modulus (E) of **CDO** films through chemically induced cross-linking. Composition and FTIR measurements suggest the presence of C-C and C-Si cross-linking with concurrent observation of improved film **hardness** and modulus at relatively low deposition temperatures. Films deposited at 373°C using diethoxy-methyl-oxiranyl have a **hardness** and modulus of 2.5 **GPa** and 18.1 **GPa**, respectively. Films deposited at 180°C using tetramethylcyclotetrasiloxane (TMCTS) and 25% hardener have **hardness** and modulus of 1.5 **GPa** and 9.4 **GPa**, respectively. These film properties are significantly higher than those observed for TMCTS alone under similar deposition conditions. Based on these results a low temperature process with 25% hardener and 75% TMCTS combined with a porogen was used to produce a porous film with a $k < 2.5$ and a **hardness** of 0.72 **GPa**.

Descriptors

DIELECTRIC-THIN-FILMS; ELASTIC-MODULI; FOURIER-TRANSFORM-SPECTRA; **HARDNESS**; INFRARED-SPECTRA; ORGANIC-COMPOUNDS; PERMITTIVITY; PLASMA-CVD; POROUS-MATERIALS.

Classification codes

A6860 Physical-properties-of-thin-films-nonelectronic*;
A8140J Elasticity-and-anelasticity;
A6220D Elasticity-elastic-constants;
A8140N Fatigue-embrittlement-and-fracture;
A6220M Fatigue-brittleness-fracture-and-cracks;
A7755 Dielectric-thin-films;
A7720 Dielectric-permittivity;
A7830G Infrared-and-Raman-spectra-in-inorganic-crystals;
A7865P Optical-properties-of-other-inorganic-semiconductors-and-insulators-thin-films-low-dimensional-structures;
A6825 Mechanical-and-acoustical-properties-of-solid-surfaces-and-interfaces;
A8115H Chemical-vapour-deposition;
A6855 Thin-film-growth-structure-and-epitaxy;
A5275R Plasma-applications-in-manufacturing-and-materials-processing;
B0520F Chemical-vapour-deposition*.

Keywords

DataStar Documents

chemical-method; elastic-modulus; **film**-hardness; PECVD-low-k-thin-films; mechanical-properties; integrated-circuits; carbon-doped-oxide-dielectrics; low-k-precursors; **CDO**-films; chemically-induced-cross-linking; composition-measurement; FTIR-measurement; C-C-cross-linking; C-Si-cross-linking; diethoxy-methyl-oxiranyl; tetramethylcyclotetrasiloxane; porous-film; porogen; film-properties; deposition-temperatures; 373-degC; 180-degC.

Treatment codes

X Experimental.

Numerical indexing

temperature: 6.46E02 K.

temperature: 4.53E02 K.

Language

English.

Publication type

Conference-proceedings.

Publication year

2004.

Publication date

20040000.

Edition

2005011.

Copyright statement

Copyright 2005 IEE.

((c) The Institution of Engineering & Technology)

Search Strategy

No.	Database	Search term	Info added since	Results
-----	----------	-------------	------------------	---------

Saved: 09-Jan-2007 21:12:48 MET